

Window Components



**Travel Restrictors**  
Provide enhanced security and safety for your vertical sliding sash windows. Used to restrict the opening of the window to just 100mm. Key operated.



**Sash Locks**  
Lock both bottom and top sashes firmly in place when the window is fully closed. Key lockable. One Sash Lock is fitted to windows up to 799mm wide. Two are fitted on windows 800mm wide and over.



**Security Bar**  
This specially-designed feature is an integral part of the window cill which significantly increases security, to help prevent potential intruders using tools or excessive force to try and lever open the bottom sliding sash and gain entry.



Window components to be finished in white.



**D Handles**  
These optional easy-grip handles can be used in place of pole eyes or sash lifts and can be fitted externally on the bottom of the top sash for ease of operation.



**Pole Eyes**  
Used for opening and closing the top sash. One Pole Eye is fitted to windows up to 479mm wide. Two are fitted on windows 480mm wide and over.



**Tilt Knobs**  
Allow inward tilting of the sliding sashes for easy and safe cleaning from inside the home. Two Tilt Knobs are fitted as standard.



**Toughened Glass**  
Fitted in both top and bottom sashes as standard.



**Sash Lifts**  
Used for opening and closing the bottom sash. One Sash lift is fitted to windows up to 479mm wide. Two are fitted on windows 480mm wide and over.

ECOSlide Window Details:

Window Style: Sliding Sash - Six-over-six glazed panels.

Finish: Crystal White



NR Design Seviles Ltd  
30 Salterbeck Terrace, Workington, Cumbria, CA145HP  
Email: nathan-routledge@live.com  
Tel: 01946 458386  
Mob: 07568 179916

- Notes:
1. All drawings are preliminary unless stated otherwise . Preliminary drawings are not to be built or manufactured from.
  2. All dimensions on the drawings should be checked on site with accurate site dimensions by the builder or client before the commencement of works.
  3. All works are subject to a qualified structural engineer reviewing the project before the commencement of works and providing structural calculations before building work commences.
  4. These plans may be subject to Planning & Building Regulation Approval or any other statute in law before the commencement of building works.
  5. All materials to match existing unless otherwise stated.
  6. Client must establish the exact position of the boundary line or party wall position, so that any extension, loft conversion or any other structure is built within the curtilage of the clients land. Any roof overhangs or other protrusions must be within this curtilage. Dimensions on the drawings should always follow site dimensions, but building or structures should not be larger that what is quoted on the drawing, so that compliance with planning permission is maintained.
  7. A CCTV survey should be carried out to establish the exact location of all drains along with a review of the asset location map. A building over agreement should be in place before work commences.
  8. Ensure all Party Wall Notices have been served and Awards/ Agreements are in place before the commencement of works.

CLIENT:  Mr Bryan Whittam			
SITE:  Ghyll Farmhouse Egremont Cumbria CA222UA			
TITLE:  ECOSlide Window Details			
SCALE AT A3: NTS	DATE: 04/05/22	DRAWN: NR	
PROJECT NO: 0422-005	DRAWING NO: 006	REVISION:	A