





PROPOSED DRAWING BASED ON ARCHITECTURAL LAYOUT RECEIVED FROM THE DEVELOPER.

DIAGRAM REFERENCES RELATE TO THE TRAFFIC SIGNS MANUAL CHAPTER 5: ROAD ALL WHITE LINING AND ROAD MARKINGS ARE TO BE IN ACCORDANCE WITH THE CURRENT EDITION OF THE TRAFFIC SIGNS MANUAL. DIAGRAM 1003A: MARK=0.6m, GAP=0.3m, WIDTH=0.2m

DIAGRAM 1004: MARK=4.0m, GAP=2.0m, WIDTH=0.1m
 DIAGRAM 1009A: MARK=0.6m, GAP=0.3m, WIDTH=0.1m
 DIAGRAM 1023A: MARK=1.25m, LENGTH=3.75m

ROAD SIGN INFORMATION

ROAD MARKING INFORMATION

DIAGRAM REFERENCES RELATE TO THE TRAFFIC SIGNS REGULATIONS & GENERAL DIRECTIONS (TSRGD) 2016. ALL SIGNS TO BE IN ACCORDANCE WITH THE CURRENT EDITION OF THE TSRGD. 2 NO. SIGNS REF DIA. 602 REQUIRED TO BE POSITIONED A 2.1m HIGH FROM GROUND LEVEL
SHEAR NUTS MUST BE USED WHEN ERECTING THE SIGN. MINIMUM LATERAL CLEARANCE IS 0.5M.

15mm WIDF STRIPS OF EDPM MATERIAL MUST BE USED BETWEEN THE LAMP COLUMN AND THE

•	15mm WIDE STRIPS OF EDPM MATERIAL MUST BE USED BETWEEN THE LAMP SIGN BRACKETS TO PREVENT DAMAGE TO THE COLUMN.	
	Sign Ref: 602	x-Height: 100
	Letter Colour: Black	Sign Face
	Background: White	Width: 600mm
	Border: Red	Height: 655mm
	Material: Class R2(12899-1:2007) P.C.S.	Area 0.51Sqm

ALL WORKS TO COMPLY WITH CURRENT VERSION OF THE FOLLOWING DOCUMENTS: DESIGN MANUAL FOR ROADS AND BRIDGES (DMRB) SPECIFICATION FOR HIGHWAY WORKS (SHW) LOCAL AUTHORITY DESIGN GUIDE AND SPECIFICATION PRIOR TO COMMENCING WORKS THE CONTRACTOR SHOULD INVESTIGATE AND LOCATE AS NECESSARY ANY STATUTORY UNDERTAKERS EQUIPMENT WITHIN THE NEW ACCESS AND DISCUSS REQUIREMENTS FOR LOWERING/DIVERSION AND PROTECTION WITH THE RELEVANT UNDERTAKER. ALL WORKS WITHIN THE PUBLIC HIGHWAY TO MEET LOCAL AUTHORITY REQUIREMENTS. CONTRACTOR TO APPLY FOR ROAD OPENING NOTICES ETC AS REQUIRED. CONTRACTOR TO CHECK ALL DIMENSIONS ON SITE. DISCREPANCIES MUST BE REPORTED TO THE DESIGNER BEFORE PROCEEDING. ONLY FIGURED DIMENSIONS ARE TO BE WORKED FROM. ALL DIMENSIONS ARE IN M, UNLESS NOTED OTHERWISE. 0. THIS DRAWING IS TO BE READ IN CONJUNCTION WITH ALL OTHER INFORMATION BY RELEVANT PARTIES CLASSED AS DESIGNERS UNDER THE CONSTRUCTION (DESIGN & MANAGEMENT) REGULATIONS 2015. ALL LEVELS ARE IN METERS, UNLESS NOTED OTHERWISE. CBR VALUE NOT AVAILABLE. ROAD CONSTRUCTION DETAIL SUBJECT TO CONFIRMATION OF CBR VALUES. CONTRACTOR TO ALLOW FOR LAB TESTS TO BE UNDERTAKEN IN AGREEMENT WITH LOCAL AUTHORITY HIGHWAY ENGINEER PRIOR TO WORKS COMMENCING. SLOPES GREATER THAN 1 IN 6 MAY REQUIRE STABILISATION. GEOTECHNICAL ENGINEER TO BE CONTACTED TO CONFIRM REQUIREMENTS. TRAFFIC SIGN DIAGRAM REFERENCES RELATE TO THE TRAFFIC SIGNS REGULATIONS & GENERAL DIRECTIONS (TSRGD) 2016. ALL SIGNS TO BE IN ACCORDANCE WITH THE CURRENT EDITION OF THE TSRGD. WHITE LINING DIAGRAM REFERENCES RELATE TO THE TRAFFIC SIGNS MANUAL CHAPTER 5: ROAD ALL WHITE LINING AND ROAD MARKINGS ARE TO BE IN ACCORDANCE WITH THE CURRENT EDITION OF THE TRAFFIC SIGNS MANUAL. SUBJECT TO LOCAL AUTHORITY APPROVAL

HEALTH & SAFETY:

1. CONTRACTOR SHOULD BE AWARE OF GENERAL CONSTRUCTION RISKS TO PREVENT SLIPS, TRIPS AND FALLS AND TAKE NECESSARY PRECAUTIONS WITHOUT SPECIAL INSTRUCTION. ROADS & DRAINAGE
2. CONTRACTOR TO PROVIDE TRENCH SUPPORTS AS APPROPRIATE AND ENSURE THAT PLANT REMAINS A SAFE DISTANCE FROM TRENCHES PRIOR TO INSTALLING DRAINAGE

3. THE TIME THAT EXCAVATIONS ARE OPEN ON SITE SHOULD BE KEPT TO A MINIMUM AND ALL TRENCHES

4. CONNECTIONS TO EXISTING SEWERS TO BE MADE BY APPROVED CONTRACTOR ONLY.

5. CONTRACTOR TO MAKE OPERATIVES AWARE OF ASSOCIATED DANGERS TO HEALTH SUCH AS LEPTOSPIROSIS (WEILS DISEASE) AND RECOMMENDED PRECAUTIONS. ADEQUATE WELFARE FACILITIES AND PROTECTIVE CLOTHING TO BE PROVIDED AS REQUIRED.

6. UNFINISHED MANHOLES MUST BE COVERED WITH LOAD BEARING MATERIALS AND SURROUNDED WITH PARBUED.

BARKIEK.

PIPES & CABLES

7. CONTRACTOR TO OBTAIN ALL SERVICE RECORDS PRIOR TO WORKS COMMENCING.

8. SERVICE RECORDS TO BE REFERRED TO PRIOR TO WORK COMMENCING. CONTRACTOR TO PROCEED WITH CAUTION AND SERVICES TO BE LOCATED BY HAND DIG AND PROTECTED ACCORDINGLY.

EXCAVATION/FILL

9. CONTRACTOR TO ENSURE RELEVANT MEASURES ARE TAKEN TO KEEP PLANT AND PEOPLE A SAFE DISTANCE FROM STEEP SLOPES DURING THE WORKS.

10. CONTRACTOR TO ENSURE THAT PROCEDURES ARE IN PLACE TO KEEP PEOPLE A SAFE DISTANCE FROM

11. CONTRACTOR TO REFER TO GROUND INVESTIGATION REPORT FOR CONTAMINATION TESTS AND TO PROVIDE ADEQUATE WELFARE FACILITIES AND PROTECTIVE CLOTHING AS REQUIRED.

PROPOSED ADOPTABLE CARRIAGEWAY

PROPOSED ADOPTABLE SHARED SURFACE

PROPOSED BLOCK PAVED RAISED TABLE

PROPOSED ADOPTABLE FOOTWAY

SHOULD BE SURROUNDED BY A BARRIER.

WORKING PLANT WHERE NECESSARY.

