

LOCATION	CHAINAGE	EASTING	NORTHING	RADIUS	BEARING	ANGLE	ARC LENGTH	TANL
				RADIO3		ANGLE	ANC LENGTH	IANL
SP-1	0.000	297216.353	515564.659		316.02785			
TP-1a	46.133	297184.323	515597.860		316.02785			
IP-1		297168.277	515614.492	96.999		26.80260	45.376	23.11
TP-1b	91.508	297161.454	515636.573		342.83045			
TP-2a	143.505	297146.105	515686.253		342.83045			
IP-2		297134.624	515723.412	53.000		72.54355	67.105	38.892
TP-2b	210.610	297095.732	515723.607		270.28690			
IP-3		297039.439	515723.889	348.941		18.32885	111.626	56.29
TP-3b	322.236	296985.913	515706.454		251.95805			
IP-4		296965.283	515699.734	301.197		8.24037	43.319	21.697
TP-4b	365.554	296945.829	515690.127		243.71768			
JP-1	441.140	296878.057	515656.658		243.71768			
	SNMENT ROAD-2							
LOCATION	CHAINAGE	EASTING	NORTHING	RADIUS	BEARING	ANGLE	ARC LENGTH	TANL
JP-1	0.000	297178.000	515605.100		225.88763			
TP-1a	19.737	297163.829	515591.361		225.88763			
P-1		297144.301	515572.429	84.400		35.72433	52.624	27.199
TP-1b	72.361	297117.393	515568.461		261.61196			
ГР-2а	126.065	297064.264	515560.627		261.61196			
P-2		297056.086	515559.421	104.418		9.05266	16.498	8.266
TP-2b	142.563	297048.200	515556.944		252.55930			
JP-2	150.341	297040.779	515554.613		252.55930			
		•			•		•	
ALIG	SNMENT ROAD-2-T							
LOCATION	CHAINAGE	EASTING	NORTHING	RADIUS	BEARING	ANGLE	ARC LENGTH	TANL
JP-1	0.000	297133.868	515572.620		160.31217			
TP-1a	9.232	297136.978	515563.927		160.31217			
P-1	3.202	297137.794	515561.645	28.410	100.01217	9.75147	4.835	2.42
EP-1	14.067	297138.985	515559.535		150.56070			
		201.100.000	0.0000.000	I			<u> </u>	
ALIG	SNMENT ROAD-3							
LOCATION	CHAINAGE	EASTING	NORTHING	RADIUS	BEARING	ANGLE	ARC LENGTH	TANL
JP-1	0.000	297160.447	515639.831		252.83045			
TP-1a	9.541	297151.332	515637.015		252.83045			
P-1	0.041	297137.057	515632.604	195.600	202.00040	8.73605	29.824	14.94
TP-1b	39.365	297122.278	515630.413	100.000	261.56650	0.7 0000	20.02	1-1.04
TP-2a	76.104	297085.936	515625.025		261.56650			
P-2	75.704	297070.010	515622.664	204.400	201.00000	9.00720	32.133	16.10
TP-2b	108.236	297054.651	515617.839	204.400	252.55930	5.557.20	02.100	10.10
JP-2	140.420	297023.946	515608.192		252.55930			
	NMENT ROAD-10							
ALIG	CHAINAGE	EASTING	NORTHING	RADIUS	BEARING	ANGLE	ARC LENGTH	TANL

6.000

6.000

JUNCTION DETAILS : ROAD-10 - ROAD-1 RH Side
Curve 2 E

Centre 02 : 297058.255 515712.728

Centre 02 : 297068.698 515630.331

Centre 02 : 297128.672 515562.207

Start TP3: 297057.624 515718.695 93.887

6.000

End TP4: 297064.207 515713.482 93.871


End TP4: 297070.029 515624.481 93.063

Start TP3: 297127.146 515568.010 90.270 End TP4: 297134.321 515564.228 89.849

250 250 250 250 251 243 243 243 243 243 243 243 243
256 242 242 256 241 256 257 241 258 258 241
204 205 206 207 208 236 237 2: 208 236 237 2: 208 236 237 2: 208 236 237 2: 208 236 237 2: 208 236 237 2: 208 236 237 2: 208 236 237 2: 208 236 237 2: 208 236 237 2: 208 238 238 238 238 238 238 238 238 238 23
195
FFL 93.25 FFL 92.75 161 220 160 NY FFL 92.75 161 220 NY FFL 93.10 NY NY FFL 93.10 NY NY FFL 93.10 NY NY FFL 93.10 NY NY NY NY NY NY NY N
159 159 159 159 159 159 159 159 159 159
150 154 153 153 154 153 155 155 155 155 155 155 155 155 155
FFL 90.85 ado NHT 145 146 148 149 149

Design based on Layout:
Edgehill Park, Whitehaven Site Layout
Plan, 3b Master dated 24.08.22

Grid/Level datum based on Topo: 230720-EHP-SH-TOPO-001, Edgehill Park Topographic Survey, dated 23.07.20 Rev: -



KEY PLAN

Coopers Drawing List:

7503-3B / 01 Proposed Drainage Layout
7503-3B / 02 Proposed Highway Setting Out
7503-3B / 03 Proposed Highway Layout
7503-3B / 04 Proposed Highway Longsections
7503-3B / 05 Highway Construction Details
7503-3B / 06 S38 Agreement Plan
7503-3B / 07 External Works Layout
7503-3B / 08 Private Drainage Layout

7503-3B / 07 External Works Layout
7503-3B / 08 Private Drainage Layout
7503-3B / 09 Drainage Construction Details.
7503-3B / 10 Manhole Schedules

7503-3B / 11 Surface Water Manhole Details
 7503-3B / 12 Surface Water Catchment Areas
 7503-3B / 13 Proposed Cut and Fill Earthworks

7503-3B / 14 Surface Finishes

<u>Notes</u>

- 1. This drawing is to be read in conjunction with all relevant approved Architects/Planning/Designers drawings and details.
- 2. Setting out shall be undertaken using only the information given.
 Distances should not be scaled from this drawing.
- It is the responsibility of the Contractor to verify all information given with regards to existing services and drainage connections etc. prior to commencing the works. The rates shall include for hand dig around services where necessary. The Contractor shall adhere to the CDM Regulations at all times
- 4. The Contractor shall comply with the following:-
- (a) All operations should be carried out in accordance with the General Health and Safety Policy of the Developer as required by Sections 2 of the Health and Safety at Work Act 1974 and in particular the Construction (General Provisions) Regulations.
- (b) The Local Authority and service companies are to be notified prior to commencement of work on site.
- (c) Prior to construction the actual positions and depths of services likely to be affected by the works should be established by means of hand dig in close liaison with the service companies. The Contractor shall immediately advise the Adopting Engineer of any services exposed which may affect the design.
- (d) All operatives working on the highway must have street works accreditation. Which must be first checked and approved by the Highways Authority before any works are commenced.
- The Contractor and/or Developer are entirely responsible for compliance with the Health and Safety at Work Act. He shall be specifically responsible for all temporary works and for the stability of the affected land and structures.
- 6. CBR values to be determined on site with the Highways Authority at the time of construction and CBR testing carried out as necessary by an independent UKAS laboratory.
- 7. The Contractor shall check all road and pavement levels before commencing the permanent adoptable works. The Adopting Engineer shall be informed immediately if any levels do not tie-in or will lead to areas of standing water. If this occurs the Developer will have to correct such problems, at his own cost, after first agreeing the necessary remedial measures required with the Adopting Engineer.
- 8. No limestone aggregate to be permitted in any wearing courses whether permanent wearing course or temporary.
- 9. All materials to be kite marked where applicable.
- 10. All final wearing courses must only be laid once construction operations on site have been completed. All permanent kerbing shall not be installed until the final wearing course is ready for laying and all permanent kerb lines must first be approved by the Adopting Engineer accordingly. All delivery tickets will be provided for all wearing course material laid.
- 11. The final thickness of sub-base materials required shall be determined by on site tests to the approval of the Engineer. Soft spots below formation and unsatisfactory sub-grade materials shall be excavated and replaced with selected fill Type 1 material to formation level.
- 12. Bitumen Materials shall comply with BS EN 13108-1
- 13. Hot bond coat to be applied between flexible carriageway layers and joints over banded.
- 14. Minimum 500mm carriageway construction for non frost susceptible protection.
- 15. Refer to Coopers Drawing No.7503-3A / 05 for highway construction details

APPROVAL

ev. Date Revision By Appd.

COOPERS

chartered consulting engineers

Tel: 01244 684910 Email: admin@coopers.co.uk Web: http://coopers.co.uk Park House Sandpiper Court Chester Business Park Chester CH4 9QU

PW AJ

Sto

26.08.22 Updated to suit revised layout

HOMES

Project

EDGEHILL PARK, CUMBRIA, PHASE 3B

Title

Proposed Highway Setting Out

 DRAWING NUMBER
 SCALE at A1
 1:500

 DATE
 04.08.22
 REVISION

 DRAWN
 PJN
 A

 CHECKED
 JAR

0 5 10 15 20 25 30 35 40 45 50 S C A L E B A R (m)

© Copyright The original of this drawing contained coloured symbols and/or features. Any black and white reproduction should not be relied upon.

Centre 01 : 297075.018 515714.082

Centre 01 : 297085.242 515633.414

Centre 01 : 297144.467 515567.931

Start TP1: 297074.683 515720.072 94.175 End TP2: 297069.065 515713.327 93.858

Start TP1: 297079.289 515632.659 93.003

End TP2: 297086.121 515627.479 93.170

Start TP1: 297141.920 515573.364 89.845 End TP2: 297138.818 515565.910 89.911