



Louvered Steel Door Armourdoor AD30

Detailed description

Louvred steel door manufactured from 1.2 mm thick corrosion resistant Zintec/ Aluzinc.

Door blades set at 45° and mounted at 50 mm deep angle frame, which is mounted on a box section sub-frame. Door frame folded from 1.6 mm Zintec/ Aluzinc. Variable subframe supplied to accommodate site tolerance of $\pm 0-30$ mm. Frame fitted with three class 13 stainless steel hinges and two security dog bolts.

Suitable for commercial and industrial use.

Product guidance - As Standard

Door leaf thickness:

48 mm.

Operation:

Manual.

Ironmongery:

- Single leaf: Modular mortice lock.
- Double leaf: As single but with an additional flush bolt to inactive leaf.

Threshold:

- 5 mm driveable – DDA compliant.

Options

Size:

- Single opening: 690–1390 mm.
- Double opening: 1290–2600 mm.
- Height (maximum): 2900 mm.

Product specification

Manufacturer

- Name: HAG Ltd. - The Door Specialists
- Web: www.hag.co.uk
- Email: info@hag.co.uk
- Tel: +44 (0)800 072 3444

HAG Ltd. - The Door Specialists



THE DOOR SPECIALISTS

HAG Ltd. - The
Door Specialists 1
Oak Lane
Fishponds Bristol
BS5 7UY

Tel: +44 (0)800 072 3444

www.hag.co.uk
info@hag.co.uk



- Fax: +44 (0)117 965 7773

- Address: 1 Oak Lane, Fishponds, Bristol BS5 7UY

Product reference Steel Door Armourdoor Louvered AD30

Size As schedule – Door Schedule.

Finish Powder coated – White RAL 9010.

Ironmongery [_____]

Accessories [None]
[Galvanized bird and vermin mesh]
[Panic bolt]
[Side and over panels]