

Proposed galvanised heavy duty tubular steel lighting column of 6.0 metre nominal height with a planted base with glass flake root protection. Column to be manufactured to: EN 40, BS EN 1461 & BS 5649

standards as supplied by Mallatite, CU Phosco, Valmont Stainton or similar.

Refe to lighting column manufacturer guidelines and technical datasheets for weight and windage of 18kg Sierra solar

Luminaire Type:

3000k Wide Road Type 1 solar luminaire

DW Windsor Sierra Solar Midi 30w

Mounting Type:

Post top mounted at 0° tilt 5.66klm

Luminaire Wattage: 30w

Warm White (3000k) Luminous Intensity:

Control Type: Motion Sensor + Dawn/Dusk sensor

UNIT IDENTIFICATION KEY:

SL** Proposed solar lighting column identification number

ISOLUX CONTOUR KEY (AT GROUND LEVEL):

0.20 Isolux contour line 0.60 Isolux contour line

1.00 Isolux contour line

2.00 Isolux contour line



R1	NEW LAYOUT 21/01/2025	21/01/2025	SRH
R0	INITIAL DESIGN FOR REVIEW AND COMMENT	12/09/2024	SRH
REV	DESCRIPTION	DATE	BY
	CLIF		

info@shdlighting.co.uk ☎ 07834 490 192 🖳 www.shdlighting.co.uk

SCHEME:	DALZELL STREET, MOOR ROW		
DRAWING:	SOLAR LIGHTING DESIGN		
CLIENT:	ABCUMBRIA		
DDAWING	SHD1718 -SHD-HLG-DALZ-DR-EO-Lighting Layout-R1	DRAWN:	SRH

PRELIMINARY DESIGN - NOT FOR CONSTRUCTION