



New product of the year -
Link Vent 4000

Window component
of the year

Link Vent 4000

4000 VENT

Equivalent Area 4000mm² EQA Equivalent Area (Route Height) 13mm 4000mm² EQA Free Area 3954.4mm² Acoustic D n,e,w (+/-) - vent open Rout Height 13mm: 32* (-1;1) Acoustic D n,e,w (+/-) - vent closed Rout Height 13mm: 41* (0;0)

Internal				External								Ventilator			
Ventilator				Canopy				Grille (Timber, Sliding door, Sash)							
H (mm)	L (mm)	D (mm)	Weight (gram)	H (mm)	L (mm)	D (mm)	Weight (gram)	H (mm)	L (mm)	D (mm)	Weight (gram)	Attachment type	Rout H (mm)	Rout L (mm)	Stand W (mm)
18.5	380	15	21.32	18.5	380	25	39.90	20	383	5.8	9.84	Clip or Screw	13	348	14

EQUIVALENT AREA – 4000 vent (4000EQA)

AIR LEAKAGE – 4000 vent **TBC** m³/h **TBC** L/s

WATERTIGHTNESS TEST TO BS EN 13141-1 – 4000 vent – Resistant to water penetration using method 1A meeting Class 9A requirement up to and at 750pa in BS EN 12208

DB RATING – BS EN ISO 10140-1:2016 (Earlier standards are withdrawn) and BS EN ISO 10140-2.
Test date 09/12/2022 by Building Research Establishment Ltd (BRE).

4000 ROUTING DETAIL

