

A01. These notes are intended to augment drawings and specifications. Where conflict of requirements exists the order of precedence shall be as shown in the specification. Otherwise the strictest provision shall govern.

A02. This drawing to be read in conjunction with all other relevant engineers and architects drawings.

A03. Drawings not to be scaled. All dimensions to be checked on site by the contractor. Any discrepancies to be notified to the Engineer and further instructions obtained before work is commenced.

No part of this drawing may be reproduced, stored in a retrieval system or transmitted in any form or by any means without prior permission in writing from RAB Engineering LTD

Manhole construction - refer to CPA technical bulletin Sept 2001 outlining changes to relevant British Product Standards BS5911-200:1994. All precast concrete products are to be kitemarked or they will be rejected as part of an adoptable system. Manhole cover slabs to BS5911

Manhole covers to have a clear opening of 600 x 600mm and shall be class D400 to BS EN124 with 150mm deep frames.

Filled ground must be filled and consolidated under the supervision of ST before any sewer works are carried out. All adoptable sewers to be BSI kitemarked, (certified to WIS-4-35-01)

Plastic channels are not acceptable

All custom built ironwork to be hot dipped galvanised prior to final fitting.

Adoptable sewer pipes to be laid in max 3m lengths unless there is a specific operational need to lay longer lengths.

United Utilities are not obliged to accept filter drain / land drainage runoff into the public sewer network or adoptable drainage network (directly or indirectly). An alternative method of disposal of land drainage runoff will therefore be required and you will have to liaise with the Local Authority, Land Drainage Section with regard to the disposal of the filter drain/land drainage run-off.

Cover slabs must carry the BSI Kitemark or will be rejected by United Utilities Inspector. Where the clear opening of the Kitemarked product is different to that of the cover and frame, a loading bearing slab should be fitted above the cover slab to bring the size down to 600mm x 600mm for the United Utilities specified cover size. Please refer to Concrete Pipe Systems Association (CPSA), 'Technical Bulletin' issued Autumn 2004 for Kitemarked cover slab opening sizes.

Sulphate resistant cement (C20-DC2) and precast concrete products must be used or a laboratory report provided proving that such precautions are not necessary.

*Sewers must have 5 metres clearance from trees and hedges (please also refer to Figure 2.3 on page 33 in "Sewers for Adoption" 6th Edition for restrictions on tree planting adjacent to sewers).

Sewers to be laid in class S bedding (150mm granular bed and surround. Where depth of cover is less than 1.2m in highways and verges (or less than 900mm in non vehicle access areas) then a concrete slab should be provided above the granular bed and surround.

The chamber size of manholes with more than one connection in them may need to be increased one increment to accommodate the connection and bends. See individual manhole detail


Contractors should be aware of significantly large diameter pipes and manhole chamber rings proposed in this design and precautions should be taken in movement and placing of such items. Also to be considered is the depth of excavation of the drainage works especially the large diameter components up to 5m deep excavations.

All adoptable sewer works and materials to be in accordance with Sewers for Adoption 6th edition. The relevant British / European and United Utilities standards / requirements / addendum & Kitemarked.

The adoptable sewers shall be a min 1.0m and manholes 0.5m from the curb and service margins.

Sewers must have 5m clearance from trees and hedges see SIA6 for restrictions on tree planting / types.

Bedding and backfill material to conform with the Water Industry specification 4-08-02 (table A2)




ALL MANHOLES AND DRAINAGE COMPONENTS TO COMPLY WITH UNITED UTILITIES CURRENT STANDARD DETAILS. ANY DEVIATION BETWEEN THESE AND THE CURRENT DESIGN TO BE CLARIFIED PRIOR TO CONSTRUCTION.

OPTIONAL MANHOLE CONSTRUCTION. IN LIEU OF THE STANDARD DETAILS UNITED UTILITIES WILL ACCEPT FP MACCANN EAST-BASE PRECAST MANHOLE BASES AND FP MACCANN WIDE WALLED MANHOLE RINGS. DEVIATION FROM THESE DRAWING BY UTILIZING THE ABOVE PROJECTS MUST BE APPROVED FOR INDIVIDUAL MANHOLES BY UNITED UTILITIES PRIOR TO CONSTRUCTION

Top water level for the 50year 15min storm

K. Full redesign following layout changes and implementation of surface water storage basin 14-8-21
L. UU reference numbers added 2-8-20
H. phases 2A & 2B annotation added 16-7-20
G. Revised following UU comment 29-11-19 2-12-19
F. Details/revisions for section 104 submission 28-11-19
E. Full redesign in line with Alpha Design layout 17-10-19
D. Full redesign to incorporate northern field and tank storage 12-6-19
C. Drainage redesigned following client and UU comments. Road20 lifted to give cover to storage pipe 17-4-19
B. Foul outfall section revised, Road 22 revised, section S59-S72 added 7-3-17
A. Storage revised to D1800mm, highway vertical alignment revised. 22-5-17



12 BERRY HOLME CLOSE
SHEFFIELD S35 1AB

High Grange Developments Ltd

Mill Hill, Cleator Moor
Whitehaven
Longitudinal Sections

DRAWN BY rab

SCALE H1:500 V1:100 DATE Apr17

DRAWING No 1083-2-2

REV K

PRELIMINARY ONLY