

Window Reference			Existing External Structural Opening Size (mm) - On site measurements required prior to manufacturing of windows.		Existing Internal Measurement (mm) - On site external measurements required prior to manufacturing of windows.		Window Specification					Ironmongery Specification				Additional Comments
							Style & Finishes		Glazing Specification							
Window Number	Window Style	Window Type	Height	Width	Height	Width	Frame Style	Colour / Finish	Proposed Casement Type	Glazing Type	Glazing Finish	Ironmongery Material Finish/Appearance	Ironmongery Type / Style	Hinge Style	Restrictor Type	
GF01	Casement	01	1510	880	-	-	350A Optima 70mm	Colour to match existing	Top Hung	Double Glazing	Obscured	Brushed Stainless Steel	As Specification	As Specification	To Match Existing	All windows to follow HBN 00-10D document. Where shown on drawings allow for fixed insulated panel to meet current U-Value requirements. All glazing types to
GF02	Casement	01	1510	880	-	-	350A Optima 70mm	Colour to match existing	Top Hung	Double Glazing	Obscured	Brushed Stainless Steel	As Specification	As Specification	To Match Existing	All windows to follow HBN 00-10D document. Where shown on drawings allow for fixed insulated panel to meet current U-Value requirements. All glazing types to
GF03	Casement	01	1510	880	-	-	350A Optima 70mm	Colour to match existing	Top Hung	Double Glazing	Obscured	Brushed Stainless Steel	As Specification	As Specification	To Match Existing	All windows to follow HBN 00-10D document. Where shown on drawings allow for fixed insulated panel to meet current U-Value requirements. All glazing types to
GF04	Casement	01	1510	880	-	-	350A Optima 70mm	Colour to match existing	Top Hung	Double Glazing	Obscured	Brushed Stainless Steel	As Specification	As Specification	To Match Existing	All windows to follow HBN 00-10D document. Where shown on drawings allow for fixed insulated panel to meet current U-Value requirements. All glazing types to
GF05	Casement	01	1510	880	-	-	350A Optima 70mm	Colour to match existing	Top Hung	Double Glazing	Clear	Brushed Stainless Steel	As Specification	As Specification	To Match Existing	All windows to follow HBN 00-10D document. Where shown on drawings allow for fixed insulated panel to meet current U-Value requirements. All glazing types to
GF06	Casement	01	1510	880	-	-	350A Optima 70mm	Colour to match existing	Top Hung	Double Glazing	Obscured	Brushed Stainless Steel	As Specification	As Specification	To Match Existing	All windows to follow HBN 00-10D document. Where shown on drawings allow for fixed insulated panel to meet current U-Value requirements. All glazing types to
GF07	Casement	01	1510	880	-	-	350A Optima 70mm	Colour to match existing	Top Hung	Double Glazing	Obscured	Brushed Stainless Steel	As Specification	As Specification	To Match Existing	All windows to follow HBN 00-10D document. Where shown on drawings allow for fixed insulated panel to meet current U-Value requirements. All glazing types to
GF08	Casement	01	1510	880	-	-	350A Optima 70mm	Colour to match existing	Top Hung	Double Glazing	Obscured	Brushed Stainless Steel	As Specification	As Specification	To Match Existing	All windows to follow HBN 00-10D document. Where shown on drawings allow for fixed insulated panel to meet current U-Value requirements. All glazing types to
GF09	Casement	01	1510	880	-	-	350A Optima 70mm	Colour to match existing	Top Hung	Double Glazing	Obscured	Brushed Stainless Steel	As Specification	As Specification	To Match Existing	All windows to follow HBN 00-10D document. Where shown on drawings allow for fixed insulated panel to meet current U-Value requirements. All glazing types to
GF10	Casement	01	1510	880	-	-	350A Optima 70mm	Colour to match existing	Top Hung	Double Glazing	Clear	Brushed Stainless Steel	As Specification	As Specification	To Match Existing	All windows to follow HBN 00-10D document. Where shown on drawings allow for fixed insulated panel to meet current U-Value requirements. All glazing types to
GF11	Casement	01	1510	880	-	-	350A Optima 70mm	Colour to match existing	Top Hung	Double Glazing	Clear	Brushed Stainless Steel	As Specification	As Specification	To Match Existing	All windows to follow HBN 00-10D document. Where shown on drawings allow for fixed insulated panel to meet current U-Value requirements. All glazing types to
GF12	Casement	01	1510	880	-	-	350A Optima 70mm	Colour to match existing	Top Hung	Double Glazing	Clear	Brushed Stainless Steel	As Specification	As Specification	To Match Existing	All windows to follow HBN 00-10D document. Where shown on drawings allow for fixed insulated panel to meet current U-Value requirements. All glazing types to
GF13	Casement	03	1510	1776	-	-	350A Optima 70mm	Colour to match existing	Top Hung	Double Glazing	Clear	Brushed Stainless Steel	As Specification	As Specification	To Match Existing	All windows to follow HBN 00-10D document. Where shown on drawings allow for fixed insulated panel to meet current U-Value requirements. All glazing types to
GF14	Casement	01	1510	880	-	-	350A Optima 70mm	Colour to match existing	Top Hung	Double Glazing	Clear	Brushed Stainless Steel	As Specification	As Specification	To Match Existing	All windows to follow HBN 00-10D document. Where shown on drawings allow for fixed insulated panel to meet current U-Value requirements. All glazing types to
GF15	Casement	01	1510	880	-	-	350A Optima 70mm	Colour to match existing	Top Hung	Double Glazing	Clear	Brushed Stainless Steel	As Specification	As Specification	To Match Existing	All windows to follow HBN 00-10D document. Where shown on drawings allow for fixed insulated panel to meet current U-Value requirements. All glazing types to
GF16	Casement	01	1510	880	-	-	350A Optima 70mm	Colour to match existing	Top Hung	Double Glazing	Obscured	Brushed Stainless Steel	As Specification	As Specification	To Match Existing	All windows to follow HBN 00-10D document. Where shown on drawings allow for fixed insulated panel to meet current U-Value requirements. All glazing types to
GF17	Casement	01	1510	880	-	-	350A Optima 70mm	Colour to match existing	Top Hung	Double Glazing	Obscured	Brushed Stainless Steel	As Specification	As Specification	To Match Existing	All windows to follow HBN 00-10D document. Where shown on drawings allow for fixed insulated panel to meet current U-Value requirements. All glazing types to
GF18	Casement	02	580	760	-	-	350A Optima 70mm	Colour to match existing	Top Hung	Double Glazing	Obscured	Brushed Stainless Steel	As Specification	As Specification	To Match Existing	All windows to follow HBN 00-10D document. Where shown on drawings allow for fixed insulated panel to meet current U-Value requirements. All glazing types to

Window Reference			Existing External Structural Opening Size (mm) - On site measurements required prior to manufacturing of windows.		Existing Internal Measurement (mm) - On site external measurements required prior to manufacturing of windows.		Window Specification					Ironmongery Specification				Additional Comments
							Style & Finishes		Glazing Specification							
Window Number	Window Style	Window Type	Height	Width	Height	Width	Frame Style	Colour / Finish	Proposed Casement Type	Glazing Type	Glazing Finish	Ironmongery Material Finish/Appearance	Ironmongery Type / Style	Hinge Style	Restrictor Type	
GF19	Casement	01	1510	880	-	-	350A Optima 70mm	Colour to match existing	Top Hung	Double Glazing	Clear	Brushed Stainless Steel	As Specification	As Specification	To Match Existing	All windows to follow HBN 00-10D document. Where shown on drawings allow for fixed insulated panel to meet current U-Value requirements. All glazing types to
GF20	Casement	01	1510	880	-	-	350A Optima 70mm	Colour to match existing	Top Hung	Double Glazing	Clear	Brushed Stainless Steel	As Specification	As Specification	To Match Existing	All windows to follow HBN 00-10D document. Where shown on drawings allow for fixed insulated panel to meet current U-Value requirements. All glazing types to
GF21	Casement	02	580	760	-	-	350A Optima 70mm	Colour to match existing	Top Hung	Double Glazing	Obscured	Brushed Stainless Steel	As Specification	As Specification	To Match Existing	All windows to follow HBN 00-10D document. Where shown on drawings allow for fixed insulated panel to meet current U-Value requirements. All glazing types to
GF22	Casement	02	580	760	-	-	350A Optima 70mm	Colour to match existing	Top Hung	Double Glazing	Obscured	Brushed Stainless Steel	As Specification	As Specification	To Match Existing	All windows to follow HBN 00-10D document. Where shown on drawings allow for fixed insulated panel to meet current U-Value requirements. All glazing types to
GF23	Casement	01	1510	880	-	-	350A Optima 70mm	Colour to match existing	Top Hung	Double Glazing	Clear	Brushed Stainless Steel	As Specification	As Specification	To Match Existing	All windows to follow HBN 00-10D document. Where shown on drawings allow for fixed insulated panel to meet current U-Value requirements. All glazing types to
GF24	Casement	01	1510	880	-	-	350A Optima 70mm	Colour to match existing	Top Hung	Double Glazing	Clear	Brushed Stainless Steel	As Specification	As Specification	To Match Existing	All windows to follow HBN 00-10D document. Where shown on drawings allow for fixed insulated panel to meet current U-Value requirements. All glazing types to
GF25	Casement	02	580	760	-	-	350A Optima 70mm	Colour to match existing	Top Hung	Double Glazing	Obscured	Brushed Stainless Steel	As Specification	As Specification	To Match Existing	All windows to follow HBN 00-10D document. Where shown on drawings allow for fixed insulated panel to meet current U-Value requirements. All glazing types to
GF26	Casement	02	580	760	-	-	350A Optima 70mm	Colour to match existing	Top Hung	Double Glazing	Obscured	Brushed Stainless Steel	As Specification	As Specification	To Match Existing	All windows to follow HBN 00-10D document. Where shown on drawings allow for fixed insulated panel to meet current U-Value requirements. All glazing types to
GF27	Casement	02	580	760	-	-	350A Optima 70mm	Colour to match existing	Top Hung	Double Glazing	Obscured	Brushed Stainless Steel	As Specification	As Specification	To Match Existing	All windows to follow HBN 00-10D document. Where shown on drawings allow for fixed insulated panel to meet current U-Value requirements. All glazing types to
GF28	Casement	02	580	760	-	-	350A Optima 70mm	Colour to match existing	Top Hung	Double Glazing	Obscured	Brushed Stainless Steel	As Specification	As Specification	To Match Existing	All windows to follow HBN 00-10D document. Where shown on drawings allow for fixed insulated panel to meet current U-Value requirements. All glazing types to
GF29	Casement	02	580	760	-	-	350A Optima 70mm	Colour to match existing	Top Hung	Double Glazing	Obscured	Brushed Stainless Steel	As Specification	As Specification	To Match Existing	All windows to follow HBN 00-10D document. Where shown on drawings allow for fixed insulated panel to meet current U-Value requirements. All glazing types to
GF30	Casement	01	1510	880	-	-	350A Optima 70mm	Colour to match existing	Top Hung	Double Glazing	Obscured	Brushed Stainless Steel	As Specification	As Specification	To Match Existing	All windows to follow HBN 00-10D document. Where shown on drawings allow for fixed insulated panel to meet current U-Value requirements. All glazing types to
GF31	Casement	01	1510	880			350A Optima 70mm	Colour to match existing	Top Hung	Double Glazing	Obscured	Brushed Stainless Steel	As Specification	As Specification	To Match Existing	All windows to follow HBN 00-10D document. Where shown on drawings allow for fixed insulated panel to meet current U-Value requirements. All glazing types to
GF32	Casement	01	1510	880			350A Optima 70mm	Colour to match existing	Top Hung	Double Glazing	Obscured	Brushed Stainless Steel	As Specification	As Specification	To Match Existing	All windows to follow HBN 00-10D document. Where shown on drawings allow for fixed insulated panel to meet current U-Value requirements. All glazing types to
FF1	Casement	01	1510	880			350A Optima 70mm	Colour to match existing	Top Hung	Double Glazing	Clear	Brushed Stainless Steel	As Specification	As Specification	To Match Existing	All windows to follow HBN 00-10D document. Where shown on drawings allow for fixed insulated panel to meet current U-Value requirements. All glazing types to
FF2	Casement	01	1510	880			350A Optima 70mm	Colour to match existing	Top Hung	Double Glazing	Clear	Brushed Stainless Steel	As Specification	As Specification	To Match Existing	All windows to follow HBN 00-10D document. Where shown on drawings allow for fixed insulated panel to meet current U-Value requirements. All glazing types to
FF3	Casement	01	1510	880			350A Optima 70mm	Colour to match existing	Top Hung	Double Glazing	Obscured	Brushed Stainless Steel	As Specification	As Specification	To Match Existing	All windows to follow HBN 00-10D document. Where shown on drawings allow for fixed insulated panel to meet current U-Value requirements. All glazing types to
FF4	Casement	02	580	760			350A Optima 70mm	Colour to match existing	Top Hung	Double Glazing	Clear	Brushed Stainless Steel	As Specification	As Specification	To Match Existing	All windows to follow HBN 00-10D document. Where shown on drawings allow for fixed insulated panel to meet current U-Value requirements. All glazing types to
FF5	Casement	02	580	760			350A Optima 70mm	Colour to match existing	Top Hung	Double Glazing	Clear	Brushed Stainless Steel	As Specification	As Specification	To Match Existing	All windows to follow HBN 00-10D document. Where shown on drawings allow for fixed insulated panel to meet current U-Value requirements. All glazing types to

Window Reference			Existing External Structural Opening Size (mm) - On site measurements required prior to manufacturing of windows.		Existing Internal Measurement (mm) - On site external measurements required prior to manufacturing of windows.		Window Specification					Ironmongery Specification				Additional Comments
							Style & Finishes		Glazing Specification							
Window Number	Window Style	Window Type	Height	Width	Height	Width	Frame Style	Colour / Finish	Proposed Casement Type	Glazing Type	Glazing Finish	Ironmongery Material Finish/Appearance	Ironmongery Type / Style	Hinge Style	Restrictor Type	
FF6	Casement	02	580	760			350A Optima 70mm	Colour to match existing	Top Hung	Double Glazing	Clear	Brushed Stainless Steel	As Specification	As Specification	To Match Existing	All windows to follow HBN 00-10D document. Where shown on drawings allow for fixed insulated panel to meet current U-Value requirements. All glazing types to
FF7	Casement	02	580	760			350A Optima 70mm	Colour to match existing	Top Hung	Double Glazing	Clear	Brushed Stainless Steel	As Specification	As Specification	To Match Existing	All windows to follow HBN 00-10D document. Where shown on drawings allow for fixed insulated panel to meet current U-Value requirements. All glazing types to
FF8	Casement	01	1510	880			350A Optima 70mm	Colour to match existing	Top Hung	Double Glazing	Clear	Brushed Stainless Steel	As Specification	As Specification	To Match Existing	All windows to follow HBN 00-10D document. Where shown on drawings allow for fixed insulated panel to meet current U-Value requirements. All glazing types to
FF9	Casement	01	1510	880			350A Optima 70mm	Colour to match existing	Top Hung	Double Glazing	Clear	Brushed Stainless Steel	As Specification	As Specification	To Match Existing	All windows to follow HBN 00-10D document. Where shown on drawings allow for fixed insulated panel to meet current U-Value requirements. All glazing types to
FF10	Casement	01	1510	880			350A Optima 70mm	Colour to match existing	Top Hung	Double Glazing	Clear	Brushed Stainless Steel	As Specification	As Specification	To Match Existing	All windows to follow HBN 00-10D document. Where shown on drawings allow for fixed insulated panel to meet current U-Value requirements. All glazing types to
FF11	Casement	01	1510	880			350A Optima 70mm	Colour to match existing	Top Hung	Double Glazing	Clear	Brushed Stainless Steel	As Specification	As Specification	To Match Existing	All windows to follow HBN 00-10D document. Where shown on drawings allow for fixed insulated panel to meet current U-Value requirements. All glazing types to
FF12	Casement	02	580	760			350A Optima 70mm	Colour to match existing	Top Hung	Double Glazing	Clear	Brushed Stainless Steel	As Specification	As Specification	To Match Existing	All windows to follow HBN 00-10D document. Where shown on drawings allow for fixed insulated panel to meet current U-Value requirements. All glazing types to
FF13	Casement	02	580	760			350A Optima 70mm	Colour to match existing	Top Hung	Double Glazing	Clear	Brushed Stainless Steel	As Specification	As Specification	To Match Existing	All windows to follow HBN 00-10D document. Where shown on drawings allow for fixed insulated panel to meet current U-Value requirements. All glazing types to
FF14	Casement	02	580	760			350A Optima 70mm	Colour to match existing	Top Hung	Double Glazing	Clear	Brushed Stainless Steel	As Specification	As Specification	To Match Existing	All windows to follow HBN 00-10D document. Where shown on drawings allow for fixed insulated panel to meet current U-Value requirements. All glazing types to
FF15	Casement	02	580	760			350A Optima 70mm	Colour to match existing	Top Hung	Double Glazing	Clear	Brushed Stainless Steel	As Specification	As Specification	To Match Existing	All windows to follow HBN 00-10D document. Where shown on drawings allow for fixed insulated panel to meet current U-Value requirements. All glazing types to
FF16	Casement	01	1510	880			350A Optima 70mm	Colour to match existing	Top Hung	Double Glazing	Clear	Brushed Stainless Steel	As Specification	As Specification	To Match Existing	All windows to follow HBN 00-10D document. Where shown on drawings allow for fixed insulated panel to meet current U-Value requirements. All glazing types to
FF17	Casement	01	1510	880			350A Optima 70mm	Colour to match existing	Top Hung	Double Glazing	Clear	Brushed Stainless Steel	As Specification	As Specification	To Match Existing	All windows to follow HBN 00-10D document. Where shown on drawings allow for fixed insulated panel to meet current U-Value requirements. All glazing types to
FF18	Casement	01	1510	880			350A Optima 70mm	Colour to match existing	Top Hung	Double Glazing	Clear	Brushed Stainless Steel	As Specification	As Specification	To Match Existing	All windows to follow HBN 00-10D document. Where shown on drawings allow for fixed insulated panel to meet current U-Value requirements. All glazing types to
FF19	Casement	01	1510	880			350A Optima 70mm	Colour to match existing	Top Hung	Double Glazing	Clear	Brushed Stainless Steel	As Specification	As Specification	To Match Existing	All windows to follow HBN 00-10D document. Where shown on drawings allow for fixed insulated panel to meet current U-Value requirements. All glazing types to
FF20	Casement	01	1510	880			350A Optima 70mm	Colour to match existing	Top Hung	Double Glazing	Clear	Brushed Stainless Steel	As Specification	As Specification	To Match Existing	All windows to follow HBN 00-10D document. Where shown on drawings allow for fixed insulated panel to meet current U-Value requirements. All glazing types to
FF21	Casement	01	1510	880			350A Optima 70mm	Colour to match existing	Top Hung	Double Glazing	Clear	Brushed Stainless Steel	As Specification	As Specification	To Match Existing	All windows to follow HBN 00-10D document. Where shown on drawings allow for fixed insulated panel to meet current U-Value requirements. All glazing types to
FF22	Casement	01	1510	880	-	-	350A Optima 70mm	Colour to match existing	Top Hung	Double Glazing	Clear	Brushed Stainless Steel	As Specification	As Specification	To Match Existing	All windows to follow HBN 00-10D document. Where shown on drawings allow for fixed insulated panel to meet current U-Value requirements. All glazing types to
FF23	Casement	01	1510	880	-	-	350A Optima 70mm	Colour to match existing	Top Hung	Double Glazing	Clear	Brushed Stainless Steel	As Specification	As Specification	To Match Existing	All windows to follow HBN 00-10D document. Where shown on drawings allow for fixed insulated panel to meet current U-Value requirements. All glazing types to match existing.

Window Reference			Existing External Structural Opening Size (mm) - On site measurements required prior to manufacturing of windows.		Existing Internal Measurement (mm) - On site external measurements required prior to manufacturing of windows.		Window Specification					Ironmongery Specification				Additional Comments
							Style & Finishes		Glazing Specification							
Window Number	Window Style	Window Type	Height	Width	Height	Width	Frame Style	Colour / Finish	Proposed Casement Type	Glazing Type	Glazing Finish	Ironmongery Material Finish/Appearance	Ironmongery Type / Style	Hinge Style	Restrictor Type	
FF24	Casement	01	1510	880	-	-	350A Optima 70mm	Colour to match existing	Top Hung	Double Glazing	Clear	Brushed Stainless Steel	As Specification	As Specification	To Match Existing	All windows to follow HBN 00-10D document. Where shown on drawings allow for fixed insulated panel to meet current U-Value requirements. All glazing types to match existing.
FF25	Casement	02	580	760	-	-	350A Optima 70mm	Colour to match existing	Top Hung	Double Glazing	Obscured	Brushed Stainless Steel	As Specification	As Specification	To Match Existing	All windows to follow HBN 00-10D document. Where shown on drawings allow for fixed insulated panel to meet current U-Value requirements. All glazing types to match existing.
FF26	Casement	01	1510	880	-	-	350A Optima 70mm	Colour to match existing	Top Hung	Double Glazing	Clear	Brushed Stainless Steel	As Specification	As Specification	To Match Existing	All windows to follow HBN 00-10D document. Where shown on drawings allow for fixed insulated panel to meet current U-Value requirements. All glazing types to match existing.
FF27	Casement	01	1510	880	-	-	350A Optima 70mm	Colour to match existing	Top Hung	Double Glazing	Obscured	Brushed Stainless Steel	As Specification	As Specification	To Match Existing	All windows to follow HBN 00-10D document. Where shown on drawings allow for fixed insulated panel to meet current U-Value requirements. All glazing types to match existing.
FF28	Casement	01	1510	880	-	-	350A Optima 70mm	Colour to match existing	Top Hung	Double Glazing	Clear	Brushed Stainless Steel	As Specification	As Specification	To Match Existing	All windows to follow HBN 00-10D document. Where shown on drawings allow for fixed insulated panel to meet current U-Value requirements. All glazing types to match existing.
SF1	Casement	02	580	760			350A Optima 70mm	Colour to match existing	Top Hung	Double Glazing	Clear	Brushed Stainless Steel	As Specification	As Specification	To Match Existing	All windows to follow HBN 00-10D document. Where shown on drawings allow for fixed insulated panel to meet current U-Value requirements. All glazing types to match existing.
SF2	Casement	02	580	760			350A Optima 70mm	Colour to match existing	Top Hung	Double Glazing	Clear	Brushed Stainless Steel	As Specification	As Specification	To Match Existing	All windows to follow HBN 00-10D document. Where shown on drawings allow for fixed insulated panel to meet current U-Value requirements. All glazing types to match existing.
SF3	Casement	02	580	760			350A Optima 70mm	Colour to match existing	Top Hung	Double Glazing	Clear	Brushed Stainless Steel	As Specification	As Specification	To Match Existing	All windows to follow HBN 00-10D document. Where shown on drawings allow for fixed insulated panel to meet current U-Value requirements. All glazing types to match existing.
SF4	Casement	02	580	760			350A Optima 70mm	Colour to match existing	Top Hung	Double Glazing	Clear	Brushed Stainless Steel	As Specification	As Specification	To Match Existing	All windows to follow HBN 00-10D document. Where shown on drawings allow for fixed insulated panel to meet current U-Value requirements. All glazing types to match existing.
SF5	Casement	02	580	760			350A Optima 70mm	Colour to match existing	Top Hung	Double Glazing	Clear	Brushed Stainless Steel	As Specification	As Specification	To Match Existing	All windows to follow HBN 00-10D document. Where shown on drawings allow for fixed insulated panel to meet current U-Value requirements. All glazing types to match existing.
SF6	Casement	01	1510	880			350A Optima 70mm	Colour to match existing	Top Hung	Double Glazing	Clear	Brushed Stainless Steel	As Specification	As Specification	To Match Existing	All windows to follow HBN 00-10D document. Where shown on drawings allow for fixed insulated panel to meet current U-Value requirements. All glazing types to match existing.
SF7	Casement	01	1510	880			350A Optima 70mm	Colour to match existing	Top Hung	Double Glazing	Clear	Brushed Stainless Steel	As Specification	As Specification	To Match Existing	All windows to follow HBN 00-10D document. Where shown on drawings allow for fixed insulated panel to meet current U-Value requirements. All glazing types to match existing.
SF8	Casement	01	1510	880			350A Optima 70mm	Colour to match existing	Top Hung	Double Glazing	Clear	Brushed Stainless Steel	As Specification	As Specification	To Match Existing	All windows to follow HBN 00-10D document. Where shown on drawings allow for fixed insulated panel to meet current U-Value requirements. All glazing types to match existing.
SF9	Casement	01	1510	880			350A Optima 70mm	Colour to match existing	Top Hung	Double Glazing	Clear	Brushed Stainless Steel	As Specification	As Specification	To Match Existing	All windows to follow HBN 00-10D document. Where shown on drawings allow for fixed insulated panel to meet current U-Value requirements. All glazing types to match existing.
SF10	Casement	01	1510	880			350A Optima 70mm	Colour to match existing	Top Hung	Double Glazing	Clear	Brushed Stainless Steel	As Specification	As Specification	To Match Existing	All windows to follow HBN 00-10D document. Where shown on drawings allow for fixed insulated panel to meet current U-Value requirements. All glazing types to match existing.

[illegible]