

Proposed Luminaire Schedule West Cumberland Phase 2 Hospital External Lighting Scheme			
Area:	Luminaire Symbol	lmage	Description
Car Parks	1A		WHITECROFT LIGHTING LEVANTER LED LAMP POST TOP LUMINARIE FOR OUTDOOR APPLICATIONS, 5725 lm, 69W, WIDE FLOOD DISTRIBUTION, IP66 MOUNTED ON 6M COLUMN, 'CCTV' DENOTES LAMP POST MOUNTED EXTERNAL CCTV CAMERA.
Street Lighting Drop off area	1B		WHITECROFT LIGHTING LEVANTER LED LAMP POST TOP LUMINARIE FOR OUTDOOR APPLICATIONS, 4669 Im, 42W, WIDE ROAD DISTRIBIUTION, IP66. MOUNTED ON 6M COLUMN. 'CCTV' DENOTES LAMP POST MOUNTED EXTERNAL CCTV CAMERA.
Walkways	<b>O</b> 1C	Î	WHITECROFT LIGHTING KOLO BOLLARD, BLACK, Robust and Weatherproof Illuminated LED Bollard, root mounted, symmetric, 3000K, 998mm nigh,410lm, 4.2W, IP66.
Lighting Outside entrances	1F		WHITECROFT LIGHTING SPECTRE WX, Wall Mounted conical luminaire for outdoor applications, IP65, 4000K, 1119Im, 9W, 3H integrated emergency.
Covered Walkway Lighting	1D	fo	WHITECROFT LIGHTING STARLINE FIXED IP67 surface opal 4000K, 635mm (297 lm; 5.7 W; 1xLED)
Main Entrance Courtyard	<b>⊘</b> 1G		WHITECROFT LIGHTING MARINE LF IN GROUND RECESSED FIXED UPLIGHTER (464 lm; 4W; 1xLED)

## DO NOT SCALE

<u>NOTES</u>

- 1. LIGHTING LEVELS REQUIRED ARE IN ACCORDANCE WITH CIBSE LG2 AND SSL LIGHTING GUIDE 6.
- 2. EXTERNAL LIGHTING TO BE CONTROLLED BASED ON EXTERNAL AMBIENT LIGHT, TIME AND MOVEMENT. EACH EXTERNAL LUMINAIRE TO BE COMPLETE WITH SMART SENSORS WHICH CAN BE WIRELESSLY LINKED TO CREATE A INTELLIGENT NETWORK WITH WEB-BASED SOFTWARE AND GRAPHIC USER INTERFACE LOCATED ON ESTATES PC.
- 3. ALLOWANCE TO BE MADE FOR A FEEDER PILLAR FOR CARPARK LIGHTING DISTRIBUTION BOARD AND CONTROLS
- 4. ALL EXTERNAL LIGHTING, BRACKETS AND COLUMNS TO BE FINISHED SUITABLE FOR USE IN A COASTAL CORROSIVE
- ENVIRONMENT. 5. POSITION OF EXTERNAL CCTV CAMERAS TO BE REVIEWED WITH TRUST.
- 6. COURTYARD LIGHTING TO BE PHOTOCELL AND TIME SWITCH CONTROLLED TO MEET TRUST PATIENT SECURITY
- REQUIREMENTS.
- EXTERNAL CCTV CAMERA, HIGH DEFINITION,
  PAN/TILT/ZOOM, IP65 MINIMUM.
  'CCTV' BY LAMP POST DENOTES LAMP POST
  MOUNTED EXTERNAL CCTV CAMERA.

POWER SUPPLY UNIT

| ISOLATOR



GRP ENCLOSURE DETAILS: 1400mm W x 660 D x REMOVABLE FLOOR 18mm PLY BACKBOARD HI/LOW VENTILATION IP65 MIN INTERNAL LIGHTING LOCK TO MATCH HOSPITAL STANDARD

P3 MAR 22 BH INCLUSION OF CIRCUIT REFERENCES

P2 MAR 22 BH ISSUED FOR STAGE 4. INCORPORATED CHANGES FROM STAGE 3 ISSUE AND CHANGES TO GROUND WORKS AND LANDSCAPING LAYOUTS

P1 JUL 21 SR ISSUED FOR STAGE 3. LIGHTING CONTROL NOTES UPDATED. FEEDER PILLAR DETAILS PO MAY 21 MP FIRST ISSUE

REV DATE BY

STAGE 4 ISSUE

SAFETY, HEALTH AND ENVIRONMENTAL INFORMATION READERS OF THIS DRAWING:
ALL EFFORTS HAVE BEEN TAKEN BY DSSR TO DESIGN OUT SIGNIFICANT HAZARDS WITHIN THE DESIGN RISK ASSESSMENT PROCESS. IT IS OUR OPINION THAT THE HAZARDS DETAILED BELOW CANNOT BE DESIGNED OUT BY US GIVEN THE CONSTRAINTS OF THE BRIEF AND ARE HIGHLIGHTED SO THAT OTHER MEANS CAN BE DEVELOPED TO MITIGATE THE RESIDUAL RISKS IDENTIFIED. MORE DETAIL AVAILABLE IN THE PROJECT SPECIFIC RISK REGISTER.

IT IS ASSUMED THAT A COMPETENT M&E CONTRACTOR OR USER WILL BE AWARE OF THE STANDARD FORESEEABLE RISKS ASSOCIATED WITH WORKING WITH THE TYPE OF SERVICES DETAILED ON THIS DRAWING.

**DSSR** | CONSULTING ENGINEERS Glasgow Harrogate London Manchester

Manchester Office
Trafford House
Chester Road
Stretford
Manchester
M32 0RS

Tel: +44 (0)161 872 4811 manchester@dssr.co.uk www.dssr.co.uk



West Cumberland Hospital Phase 2

EXTERNAL LIGHTING, POWER & CCTV LAYOUT NEW BUILT SHEET 2 0F 2

WCHPH2-DSSR-V7-SL-DR-E-90001-2.dwg